

2" INGROUND - ROUND  
2021

WAC  
LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

**PRODUCT DESCRIPTION**  
Landscape 2" recessed inground luminaire for up, down, side light applications.

- FEATURES**
- IP68 rated, Suitable for continuous immersion under water
  - Factory sealed water tight fixtures
  - Solid stainless steel construction
  - Stainless steel spring clip allows wall or downlight applications
  - Available Concrete Pour Adapter
  - Spring, and 6' lead wire and direct burial gel filled wire nuts included
  - Maintains constant lumen output against voltage drop
  - UL 1838 Listed

**SPECIFICATIONS**

**Input:** 9 - 15VAC (Transformer is required)  
**Power:** 4.1W / 6.6VA (Use VA value for sizing the transformer and calculate voltage drop.)  
**Brightness:** 245 lm  
**Beam Angle:** 25°  
**CRI:** 85  
**Rated Life:** 70,000 hours

ORDERING NUMBER		Color Temp		Finish	
2021	Round	27	2700K	BS	Bronzed Stainless Steel
		30	3000K	SS	Stainless Steel

IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and shear loads test	N/A	Yes

2021-30\_\_\_\_\_

Example: 2021-30SS

# 2" INGROUND - ROUND

## 2021

# WAC

## LANDSCAPE LIGHTING

### Magnetic Transformers



*Stainless Steel, 12-15V output,  
IP65 rated, UL 1838 listed  
See transformer spec sheet for  
details and its accessories*


**9075-TRN-SS**  
75W Max

**9150-TRN-SS**  
150W Max

**9300-TRN-SS**  
300W Max

**9600-TRN-SS**  
600W Max

### 2" Concrete Pour Kit



*For installation in concrete.  
Use with a 4" outdoor rated junction box  
and a trade size 2" schedule 80 PVC pipe*

**2000-CON-PVC**

### TESTED MAGNETIC LOW VOLTAGE (MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
<b>2021</b>	Lutron	<i>Diva</i>	<i>DVLV-600</i>	<i>600W</i>	<i>20% - 100%</i>	
		<i>Skylark</i>	<i>SLV-600P</i>	<i>600W</i>	<i>15% - 100%</i>	<i>Best performance</i>
		<i>Skylark</i>	<i>S-10P</i>	<i>1000W</i>		<i>Not recommended</i>

\*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

**Headquarters, East Manufacturing Facility**  
44 Harbor Park Drive  
Port Washington, NY 11050

**South East Manufacturing Facility**  
1600 Distribution Ct  
Lithia Springs, GA 30122

**Central Manufacturing Facility**  
1700 South J Elmer Freeway, Ste 100  
Cedar Hill, TX 75104

**West Manufacturing Facility**  
1750 S Archibald Ave  
Ontario, CA 91761