2" INGROUND - SQUARE

2052 Honeycomb Louver



LANDSCAPE LIGHTING





Fixture Type:		
Catalog Numbe	r:	
Project:		

PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for up, down, side light applications.

FEATURES

- Integrated honeycomb louver for reduced glare
- 30° visual cutoff IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Location:


Input: 9 - 15VAC (Transformer is required)

Power: 4.1W / 6.6VA (Use VA value for sizing the transformer

and calculate voltage drop.)

Brightness: 170 lm Beam Angle: 25° CRI: 85

Rated Life: 70,000 hours



IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and shear loads test	N/A	Yes

ORDERING NUMBER

		Color Temp		Finish	
2052	Square	27	2700K	BS	Bronzed Stainless Steel
	Honeycomb louver	30	3000K	SS	Stainless Steel

2052-30__

Example: 2052-30SS

AUG 2024

2" INGROUND - SQUARE

2052 Honeycomb Louver



Magnetic Transformers



Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS 150W Max **9300-TRN-SS**

9600-TRN-SS 600W Max

2" Concrete Pour Kit





For installation in concrete.
Use with a 4" outdoor rated junction box and a trade size 2" schedule 80 PVC pipe

2000-CON-PVC

TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
2052	Lutron	Diva	DVLV-600	600W	20% - 100%	
		Skylark	SLV-600P	600W	15% - 100%	Best performance
		Skylark	S-10P	1000W		Not recommended

^{*}Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.