
LANDSCAPE PENDANT LIGHT 12V

3811 / 3821 / 3831




LANDSCAPE LIGHTING





Project:

Location:



PRODUCT DESCRIPTION

Landscape 12V pendant with 3 CCT selection and adjustable beam angles, options available as hanging light or ceiling light

FEATURES

- Continuously Adjustable Beam Angles. Indexed at 35°, 45°, 55°
- IP66 rated, Protected against high-pressure water jets
- Corrosion resistant aluminum
- Factory sealed water tight fixtures
- Constant output for 9V-15V input
- $\bullet \ \mbox{Option available for hanging light or ceiling light}$
- 2700K/3000K/4000K selectable
- 10' lead wire and direct burial gel filled wire nuts included
- MLV dimmable with remote MLV dimmers
- On-board dimming with continuous brightness control

SPECIFICATIONS

Input: 9 -15VAC

Power: 1W to 7.5W / 2VA - 8VA (Use VA value for sizing

the transformer and calculate voltage drop.)

Brightness: 45 lm to 380 lm
Beam Angle: 35° to 55°
CRI: 85
Rated Life: 50,000 hours

Transformer Required (order separately)



Select Warm White, Pure White, or Cool White (2700K, 3000K or 4000K)

ORDERING NUMBER

		Color Temp		Finish	
3811-27/30/40 6' Chain included	12V	27 30 40	2700K Warm White 3000K Pure White 4000 Cool White	BK BZ	Black on Aluminum Bronze on Aluminum
3821-27/30/40 6' Chain included	12V	27 30 40	2700K Warm White 3000K Pure White 4000 Cool White	BK BZ	Black on Aluminum Bronze on Aluminum
3831-27/30/40	12V	27 30 40	2700K Warm White 3000K Pure White 4000 Cool White	BK BZ WT	Black on Aluminum Bronze on Aluminum White on Aluminum



Continuously adjustable brightness

3811-27/30/40

Example: 3811-27/30/40BZ

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters, East Manufacturing Facility** 44 Harbor Park Drive Port Washington, NY 11050 **South East Manufacturing Facility** 1600 Distribution Ct Lithia Springs, GA 30122 Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104 West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

LANDSCAPE PENDANT LIGHT 12V

3811 / 3821 / 3831



Accessories

Optics



LENS-11-AMB LENS-11-GRN LENS-11-RED

Amber Green Red

LENS-11-BLU Blue LENS-11-FR

Frosted

Enhances saturation of florals and foliage

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS 150W Max

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max



2