# WALL WASH 12V

5021



# LANDSCAPE LIGHTING

		Fixtu
		Cata
		Proj
		Loca
8	<b>  − 4</b> <sup>3</sup> / <sub>8</sub> " <b>−   − 3</b> <sup>3</sup> / <sub>4</sub> " <b>−  </b>	
" Son " VV		

xture Type:				
atalog Numbe	er:			
oject:				

Location:

### **PRODUCT DESCRIPTION**

Landscape Wall Wash luminaire

#### FEATURES

- A uniform wide distribution wall wash from a small form factor
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- Mounting stake, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmer

#### **ORDERING NUMBER**

		Color Temp		Finish	
5021	Wall wash 12V	27 30	2700K 3000K	BK BZ BBR	Black on Aluminum Bronze on Aluminum Bronze on Brass

## 5021-\_\_\_\_

### Example: 5021-30BK

SPECIFICATIONS

Input:	9 - 15VAC (Transformer is required)
Power:	2W to 16W / 2VA - 23VA (Use VA value for sizing the
	transformer and calculate voltage drop.)
Brightness:	190 lm to 980 lm
<b>Beam Angle:</b>	15° upward (50° by 80°)
CRI:	85
Rated Life:	70,000 hours

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122 West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

# WALL WASH 12V



# LANDSCAPE LIGHTING

/AC

Accessories						
Addtional Stake	9000-ST9-BZ	9000-ST9-BZ			Durable PVC stake	
Surface Mount Flange/Stake	5000-SCP-BZ 5000-SCP-BBR 5000-SCP-BK	5000-SCP-BBR		1	Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box	
Guardian Mount	9000-SP9-BZ		Stainless Steel		Heavy duty stainless steel spike to position fixture Formed from a single piece of metal	
Tree Mount Junction Box	5000-ТСР-ВZ 5000-ТСР-ВК		Bronze on Aluminur Black on Aluminum		Bronze on Aluminum box with Stainless steel mounting screws. Two $\frac{1}{2}$ " NPT threaded holes	
Gutter Mount Bracket	5000-GM-BZ 5000-GM-BK		Stainless Steel		Stainless Steel universal mounting bracket for gutter mounting fixture	
Optics	LENS-2X4-AMB LENS-2X4-GRN LENS-2X4-RED	Amber Green Red	LENS-2X4-BLU LENS-2X4-FR LENS-2X4-SPR	Blue Frosted Spread	Enhances saturation of florals and foliage	
Extension Rods	5000-X04-BZ 5000-X04-BK 5000-X04-BBR 5000-X08-BZ 5000-X08-BK 5000-X08-BBR 5000-X12-BZ 5000-X12-BK 5000-X12-BBR	4 in 4 in 8 in 8 in 8 in 12 in 12 in 12 in	5000-X18-BZ 5000-X18-BK 5000-X18-BBR 5000-X24-BZ 5000-X24-BK 5000-X24-BBR	18 in 18 in 18 in 24 in 24 in 24 in	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box	
Rod L-Coupler	5000-LCO-BZ		Bronze			

## Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

**9075-TRN-SS** 75W Max **9150-TRN-SS** 150W Max **9300-TRN-SS** *300W Max* 



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050 South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122 **Central Manufacturing Facility** 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104

9600-TRN-SS

600W Max

West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761