
GRAND INGROUND 120V

5034







Fixture Type:	
Catalog Numbe	er:
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape high output In-ground luminaire with dynamic beam changing and integral on-board dimming.

FEATURES

- Tiltable and adjustable beam angle
- Integral dimmer
- IP67 rated, protected from temporary immersion under water
- Drive over up to 4500lbs
- Solid diecast brass or corrosion resistant aluminum
- Available concrete pour kit
- 6' lead wire and direct burial gel filled wire nuts included
- · Maintains constant lumen output against voltage drop
- UL 1598 Listed

ORDERING NUMBER

		Color Temp	Finish	1
5034	Inground 120V	30 3000K	BZ BBR	Bronze on Aluminum Bronze on Brass

5034-30

Example: 5034-30BBR

SPECIFICATIONS

 Input:
 120VAC

 Power:
 4W to 24W

 Brightness:
 130 lm to 2000 lm

 Beam Angle:
 20° upward 60°

CRI: 85

Rated Life: 50,000 hours

IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and	N/A	Yes
shear loads test		

1



Rock Guard

Protects the fixture face



5830-GRD-BZBronze on Aluminum

5830-GRD-BBR *Bronze on Brass*

Concrete Pour Kit

For installation in concrete Five ½" NPT threaded holes, PC



5830-PIP-PVCShown with temporary dense foam cap