

UNDERWATER SPOT  
5511

WAC  
LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Landscape underwater spotlight is the perfect solution for fountains, ponds and all other submerged lighting applications. Featuring a durable cast brass construction that is designed to last forever, the underwater spotlight includes a 30' lead wire and is available in a Natural Brass finish.

FEATURES

- IP68 rated, Suitable for continuous immersion under water in depths up to 3'
- Factory sealed water tight fixtures
- Cast brass construction
- 30' long lead wire and direct burial gel filled wire nuts included
- Includes a detachable shroud
- Maintains constant lumen output against voltage drop
- UL 676 Listed

SPECIFICATIONS

**Input:** 9 - 15VAC (Transformer is required)  
**Power:** 10W / 11.2VA (Use VA value for sizing the transformer and calculate voltage drop.)  
**Brightness:** 780 lm  
**Beam Angle:** 60°  
**CRI:** 85  
**Rated Life:** 50,000 hours

ORDERING NUMBER

		Color Temp	Finish
5511	Underwater Spot	30 3000K	NB Natural Brass

5511-30NB

Accessories Submersible luminaires

Wall Wash Optics		<b>LENS-20-AMB</b> <b>LENS-20-GRN</b> <b>LENS-20-RED</b>	Amber Green Red	<b>LENS-20-BLU</b> <b>LENS-20-FR</b> <b>LENS-20-SPR</b>	Blue Frosted Spread	Enhances saturation of florals and foliage and turtle friendly
Direct Burial Waterproof Wire Nuts		<b>9020-WNT-BK</b>	Silicone filled wire nut with gasket (Pack of 20pcs)			

Detachable shroud and direct burial gel filled wire nuts (12V)

wacighting.com Phone (800) 526.2588 Fax (800) 526.2585	Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050	South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122	Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104	West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761
--	--	---	---	--

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed  
See transformer spec sheet for details and its accessories

**9075-TRN-SS**  
75W Max

**9150-TRN-SS**  
150W Max

**9300-TRN-SS**  
300W Max

**9600-TRN-SS**  
600W Max

